



11 ft. Service Body Datasheet

Standard Accessories and Features

- Chrome t-bar handle latches with polished stainless steel pockets and Galvaneal steel locking rods.
- Three point latching system on all compartment doors.
- Full-length, 5/16" stainless steel door shafts and hinge blocks with nylon inserts. On all compartment.
- All hinge blocks fastened with stainless steel mono bolts.
- All compartment doors equipped with barrel locks.
- Gas shocks on open top compartments.
- Seal-beam type tail and clearance lights.
- Gas shocks on all compartment doors.
- Scelzi exclusive door seal.
- All bodies equipped with a six inch step bumper.
- Bodies fastened to frame at six mounting points.
- All seams are caulked with 3M ultra pro seam sealer.
- Complete under sealing of bed and wheel wells. Multiple coats of primer and urethane paint to maintain durability.
Wiring built as harnesses and run thru loop clamps to prevent chafing and to secure mounting.
- Stainless steel tubing around wheel well openings.
- Self-leveling tailgate with stainless steel cap and guard rail. Daimond plate inner lining.

Material

- Exterior structural body panels.
- Door post: 14 Gauge Galvaneal steel.
- End caps: 14 Gauge Galvaneal steel.
- Back wrapper: 14 Gauge Galvaneal steel.
- Closed tops and open top lids: 16 Gauge Galvaneal steel.
- Flooring: 12 Gauge diamond plate.
- Bulkhead: 14 Gauge Galvaneal steel.
- Interior structural body panels.
- Door skin: 18 Gauge Galvaneal steel.
- Inner door skin: 20 Gauge Galvaneal steel.

Unacceptable Practices and Components

- Body mounting using only four points.
- Clip-in adjustable shelving.
- Single panel doors.
- Wiring running through interior of compartments.
- Shelving made from material other than 16 Gauge Galvaneal steel.
- Piano hinges on compartment doors.